

RJ-250 SC

Self-Contained Compactor
with 15 to 39 Cubic Yard
Capacity Container



Totally



Listed!



*RJ-250SC with optional
doghouse hopper.*

RJ-250SC Features

- Great for high liquid waste
- Large 40" x 58" Feed Opening
- Full Door Seal with "P" Seal
- Bubble Gate with Auto Relatch and Double-Hinge Door
- Qwik Clean® Tank
- CYCON Life-Xtender® Cyclic Control System
- Signature Series Warranty
- Unit is ***Totally UL Listed!***

AUTHORIZED DEALER:



1042 E. Fort Union #260
Midvale, UT. 84047
Ph. 801-565-1033
fax 280-565-1044

Action Compaction Equipment www.actioncompaction.com

WHY MARATHON IS THE PREFERRED CHOICE

Compare a Marathon RJ-250 with any other self-contained compactor on the market, and you'll quickly discover why Marathon is the preferred choice of discriminating buyers.

Components are selected for **longevity and minimum maintenance**, with special attention given to the selection of highly sensitive components. Stress engineering provides the optimum degree of structural integrity. Only the best materials are used. The highest standards of quality are observed in the manufacturing process. That's why you'll find Marathon Compactors "packing trash" long after other makes have failed!

The RJ-250 units are state-of-the-art in roll-off self-contained compactors featuring **oversized feed opening and expanded container storage capacity**. The RJ-250 Compactors are designed to store and transport your waste, prevent contamination of your work and public areas in accordance with public health department requirements, improve working conditions for your employees and reduce disposal costs.


Both the RJ-250SC and RJ-250HT Compactors **can be customized with a variety of loading arrangements** to suit your specific needs. The RJ-250HT is particularly well suited for security chute-fed and dock-fed applications where maneuvering space for the collection vehicle is limited. Unique to the RJ-250HT, the compactor is built into the same door through which the compacted refuse is later emptied. This eliminates the need for the additional space necessary for the time-consuming double "turn-around" maneuver required for conventional self-contained models.

RJ-250SC/RJ-250HT FEATURES:

- Exclusive **40" x 58"** feed opening to handle large, bulky items!
- **Continuous feeding capability** – even while compactor is operating!
- Adaptable to special loading systems such as large capacity hoppers, security chutes or total enclosures.
- Total odor and pest control via Marathon's Ozone Odor Control option
- Easy loading from either ground or dock level.
- Over 24 tons of crushing force to reduce refuse to a fraction of its former size **saving valuable space**.
- Fits into same space as the pace-setting RJ-100SC Ultra! Extra length roll-off hoist is not required!
- Easy and fast installation! Installation costs are cut by half over conventional compaction systems.
- Fire hose connection provided on each unit.
- Factory testing to assure leakproof construction.
- Totally **UL Listed**.

Signature Series Warranty

Featuring 3 Years Structure
2 Years Components
6 Months Labor



Dimensions not shown: 8'-4-1/8" (2543mm) Overall Width
Ground Roller Widths: 61 7/8" (1569mm) Inside Rollers
67 3/8" (1712mm) Roller Centers
72 7/8" (1851mm) Outside Rollers

Specifications:

Charge Box Capacity
[Mfrs. Rating]1.7 cu yd1.30 m³
[WASTEC Rating].....1.29 cu yd0.99 m³
Clear Top Opening.....40"L x 58"W1016 mm x 1473 mm

Performance Characteristics:

Cycle Time33 s33 s
Total Normal Force39,900 lb177 kN
Total Maximum Force49,500 lb220 kN
Normal Ram Face Pressure27.1 psi189 kPa
Maximum Ram Face Pressure33.7 psi235 kPa
Ram Penetration6"152 mm

Electrical Equipment:

Electric Motor 3/60/230-46010 hp7.5 kW
Electric Control Voltage120 VAC120 VAC
Panel Box Assembly
UL RatedKey Operated
All Circuits Fused - 3 Push Button Station/Start/Stop/Reverse


Hydraulic Equipment:

Hydraulic Pump10 gpm38 L/min
Normal Pressure1850 psi128 bar
Maximum Pressure2300 psi159 bar
Hydraulic Cylinders (2) - Bore4"102 mm
- Rod2-1/2"64 mm

RJ-250SC	A	B	C	D**	E	LBS.
15 cu yds	4' - 0" 1219mm	3' - 7-1/4" 1099mm	5' - 7-1/2" 1715mm	14' - 3" 4521mm	7' - 5" 2261mm	8,860 4019kg
20 cu yds	4' - 0" 1219mm	3' - 7-1/4" 1099mm	5' - 7-1/2" 1715mm	17' - 4" 5499mm	7' - 5" 2261mm	9,520 4318kg
25 cu yds	4' - 0" 1219mm	3' - 7-1/4" 1099mm	5' - 7-1/2" 1715mm	17' - 10" 4521mm	8' - 8" 2642mm	10,030 4550kg
30 cu yds	4' - 0" 1219mm	3' - 7-1/4" 1099mm	5' - 7-1/2" 1715mm	20' - 5" 6553mm	8' - 8" 2642mm	10,620 4818kg
34 cu yds	4' - 0" 1219mm	3' - 7-1/4" 1099mm	5' - 7-1/2" 1715mm	22' - 5" 7023mm	8' - 8" 2261mm	11,130 5049kg
39 cu yds	4' - 0" 1219mm	3' - 7-1/4" 1099mm	5' - 7-1/2" 1715mm	24' - 11-1/2" 7658mm	8' - 8" 2261mm	11,790 5348kg
RJ-250HT	A	B	C	D**	E	LBS.
25 cu yds	4' - 1" 1245mm	3' - 7-1/4" 1099mm	5' - 7-1/2" 1715mm	20' - 9-1/2" 6337mm	8' - 6" 2591mm	11,104 4173kg
29 cu yds	4' - 1" 1245mm	3' - 7-1/4" 1099mm	5' - 7-1/2" 1715mm	23' - 1" 7036mm	8' - 6" 2591mm	11,604 5264kg

* Overall height with hydraulic tailgate raised: 16'-6". Hoist should be equipped with selector valve (1500 psi minimum) in order to control hydraulic tailgate.

** Other lengths available. Call factory for details.




Patented Double-Hinge with Bronze Bushing

Every RJ-250SC is tested for water tightness before leaving the factory. Liquid retention is assured by the incredible **Double-Hinge!** It creates uniform seal compression while eliminating seal "scrubbing" and damage so often encountered with competitive designs. The **Double-Hinge**** also saves expensive driver and truck time because only one easy-to-operate ratchet makes it work.

**U.S. Patent #4741455

"P" Seal

The "P" shaped **Door Seal** is specially designed for portable compaction/containers to provide a superior water tight closure. The mounting is engineered for quick and easy installation when replacement is necessary, requiring no field fitting, cutting or welding.



Marathon's Patented...

***CYCON Cyclic Control System**

Standard on all RJ-250SC and 250HT Compactors

- Reliable, solid state circuitry eliminating all pressure and limit switches
- Extended cylinder and hose wear life – guaranteed by CYCON's no-shock cycle control
- Automatic "container full assurance system" – the ram dwells against the load at full pressure resulting in better compaction
- Smoother running, quieter operation
- Advanced hydraulic design allows the system to operate at minimum pressure levels except when actually packing solid waste
- More accurate Advanced Warning or Container Full options
- Dramatically improved cold weather performance

*U.S. Patent #4860646




The innovative **"Bubble Gate"** adds a **full cubic yard** to container capacity! Superior compaction ratios result from its special curved shape! These two unique benefits **reduce costs of disposal.**



"Bubble Gate" and "Auto Relatch"


The ultimate in latch systems, Marathon's **"Auto Relatch"** eliminates the need to hold door while operating the latch ratchet. The design allows operator to use both hands on the ratchet.



Superior to power pack mounted on the compactor, the **Remote Power Pack** remains free of damage caused by jolting during transit to and from disposal site and problems caused by severe dust conditions found at the landfills. There are no electrical connections to "make" and "break" – two simple-to-use hydraulic quick disconnects couple power unit to packing head. The **Weather Cover** for the Remote Power Pack is standard, as is the **UL and CSA rated Power Box Assembly.**



The optional doghouse offers a totally enclosed charge box with extra large door opening (42"W x 40 5/8"H) and flush lockable latch.



The **Qwik Clean® Tank** feature, standard on all RJ-250SC and RJ-250HT Compactor/ Containers, funnels any liquid seepage which can occur during compaction into an enclosed area underneath the charge box floor. The liquid is automatically discharged at the disposal site, in effect flushing the container and the area behind the ram.

The 12" high, 750 gallon capacity **sump area** is designed to provide easier hook access for roll-off drivers.

AUTHORIZED DEALER:

1042 E. Fort Union #260
Midvale, UT. 84047
Ph. 801-565-1033
fax 280-565-1044

Action Compaction Equipment www.actioncompaction.com